

Multi Grabs

IMG S - Sorting Jaws

IMG D - Demolition Sorting Jaws

IMG H - Material Handling Jaws




IMG L - Loading Jaws

IMG T - Timber Jaws



A TOOL FOR EVERY JOB

Application areas

		S	D	H	L	T
 <p>Demolition & Renovation</p>	Light demolition		<input type="radio"/>			
			<input type="radio"/>			
			<input type="radio"/>			
			<input type="radio"/>			
			<input type="radio"/>			
	Demolition of non-reinforced concrete structures		<input type="radio"/>			
			<input type="radio"/>			
			<input type="radio"/>			
	Composite steel & concrete structure demolition					
	Demolition of metallic buildings and structures					
	Sorting and loading		<input type="radio"/>	<input type="radio"/>		
			<input type="radio"/>		<input type="radio"/>	
		<input type="radio"/>		<input type="radio"/>	<input type="radio"/>	
		<input type="radio"/>		<input type="radio"/>	<input type="radio"/>	
Pavement demolition			<input type="radio"/>			
			<input type="radio"/>			
 <p>Earth Moving and Construction</p>	Earth moving works					
			<input type="radio"/>		<input type="radio"/>	
	Foundation works					
 <p>Material Handling</p>	Building construction					
			<input type="radio"/>		<input type="radio"/>	
				<input type="radio"/>	<input type="radio"/>	
			<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	
			<input type="radio"/>		<input type="radio"/>	



		S	D	H	L	T
Infrastructures	Tunnelling					
	Underwater application					
Agriculture and Forestry	Trenching					
	Road construction					
Recycling	Gardening & landscaping					
Recycling	Forestry					
Recycling	Processing					
Recycling	Handling and sorting					
Recycling	Downsizing and sorting					

IMG jaws

Years of experience have enabled Indeco to meet the specific demands of the market by designing and developing - with all our usual excellence in terms of innovation, quality and reliability - this line of equipment for a wide range of sectors, from demolition to forestry jobs. The five different models of Indeco IMG jaws run on the same hydraulic system, an upgrade compared with the previous IDG system, combined with the 360° rotation mechanism found on all of Indeco's other rotating products. Its innovative design features, specifically created to handle each product variant, and its use of special HARDOX® wear-resistant steels, have helped to combine some key features such as outstanding robustness and light weight, as well as above-average payload and gripping force. Its exceptional maneuverability, its mounting bracket compatible with other Indeco products, the efficiency of its hydraulic system which ensures maximum precision in handling and is cheap to run are just some of the extra qualities that make Indeco IMG jaws such safe and reliable partners.

Having such a wide range of models, in each of the five product variants, means there is always a perfect combination for your carrier, no matter what size it is.

IMG S - Sorting Jaws

Indeco IMG S sorting jaws are the ideal tools for sorting waste materials from demolition work; for clearing stony ground and for dredging rivers and seas.

IMG D - Demolition Sorting Jaws

Indeco IMG D demolition sorting jaws are ideal for light demolition jobs such as demolishing wood and brick structures and can also be used to select and handle waste materials. Their unique structure, outstanding maneuverability, power and high payload are ideal for recycling and recovery.

IMG H - 3+2 Material Handling Jaws

Designed to facilitate handling of large objects such as scrap metal, vehicles and other demolition scrap, IMG H jaws provide a safe, powerful grip thanks to their strong interlocking teeth and hydraulic rotation system.

IMG L - Loading Jaws


The geometry of the Indeco IMG L loading jaws is designed for maximum load, making them ideal for moving earth, gravel, sand, mud, boulders, agricultural and industrial waste, urban waste, minerals, etc.

IMG T - Timber Jaws


Designed to combine maximum gripping force with the lightest possible weight, Indeco IMG T grabs facilitate the handling of large tree trunks in forestry operations.




Features of IMG jaws




IMG S - Sorting Jaws




IMG D - Demolition Sorting Jaws



IMG H - 3+2 Material Handling Jaws



IMG L - Loading Jaws



IMG T - Timber Jaws



Technical Data	IMG 400	IMG 600	IMG 1200
Type of carrier	1 3	1 3 4	4 5
Excavator weight	6500 ÷ 22000 lbs	11000 ÷ 35500 lbs	26500 ÷ 48500 lbs
Maximum working pressure	4400 psi	4400 psi	4400 psi
Maximum oil delivery	8 gpm	13.5 gpm	19 gpm
Hydraulic connections for cylinder	1/2"	1/2"	3/4"
Maximum rotation pressure	1500 psi	1500 psi	1500 psi
Maximum rotation oil flow	3 gpm	3 gpm	5.5 gpm
Hydraulic connections for rotation	3/8"	3/8"	1/2"
Maximum force at blade/teeth	7000 lbs	9000 lbs	13500 lbs
Compatibility of attachment plate with hammer	HP 1250	HP 1250	HP 3000 - HP 4000

Sorting Jaws	IMG 400 S	IMG 600 S	IMG 1200 S
Attachment operating weight*	850 lbs	1300 lbs	2550 lbs
Load capacity	11600 in ³	19600 in ³	37900 in ³
Jaw width	36 in	43 in	52 in
Maximum opening	60 in	68 in	88 in
Depth	24 in	28 in	36 in

Demolition Sorting Jaws	IMG 400 D	IMG 600 D	IMG 1200 D
Attachment operating weight*	900 lbs	1350 lbs	2650 lbs
Load capacity	11600 in ³	19600 in ³	37900 in ³
Maximum opening	60 in	70 in	90 in
Depth	24 in	28 in	36 in

Material Handling Jaws 3+2	IMG 400 H	IMG 600 H	IMG 1200 H
Attachment operating weight*	950 lbs	1450 lbs	2850 lbs
Maximum opening	40 in	50 in	60 in
Depth	24 in	26 in	34 in

Loading Jaws	IMG 400 L	IMG 600 L	IMG 1200 L
Attachment operating weight*	950 lbs	1400 lbs	2750 lbs
Load capacity	11600 in ³	19600 in ³	37900 in ³
Maximum opening	60 in	70 in	90 in
Depth	24 in	28 in	36 in

Timber Jaws	IMG 400 T	IMG 600 T	IMG 1200 T
Attachment operating weight*	950 lbs	1400 lbs	2750 lbs
Maximum opening	40 in	50 in	60 in
Depth	24 in	26 in	34 in

*The operating weight of the equipment includes mounting bracket compatible with Indeco construction standards. Any differences in weight may be due to a different mounting bracket configuration.

Carrier key



Compact excavator



Miniloader



Backhoe loader



Wheeled excavator



Tracked excavator

Technical Data	IMG 1700	IMG 2300	IMG 2800
Type of carrier	4 5	5	5
Excavator weight	37500 ÷ 66000 lbs	48500 ÷ 88000 lbs	57000 ÷ 110000 lbs
Maximum working pressure	4700 psi	5100 psi	5100 psi
Maximum oil delivery	21.5 gpm	34.5 gpm	42.5 gpm
Hydraulic connections for cylinder	3/4"	3/4"	3/4"
Maximum rotation pressure	1600 psi	1600 psi	1600 psi
Maximum rotation oil flow	5.5 gpm	8 gpm	8 gpm
Hydraulic connections for rotation	1/2"	1/2"	1/2"
Maximum force at blade/teeth	15500 lbs	22000 lbs	26500 lbs
Compatibility of attachment plate with hammer	HP 3000 - HP 4000	HP 5000 ÷ HP 7500	HP 5000 ÷ HP 7500

Sorting Jaws	IMG 1700 S	IMG 2300 S	IMG 2800 S
Attachment operating weight*	3550 lbs	4800 lbs	5850 lbs
Load capacity	55000 in ³	82400 in ³	103800 in ³
Jaw width	58 in	65 in	69 in
Maximum opening	100 in	108 in	120 in
Depth	40 in	44 in	48 in

Demolition Sorting Jaws	IMG 1700 D	IMG 2300 D	IMG 2800 D
Attachment operating weight*	3750 lbs	5100 lbs	6200 lbs
Load capacity	55000 in ³	82400 in ³	103800 in ³
Maximum opening	100 in	110 in	120 in
Depth	40 in	44 in	48 in

Material Handling Jaws 3+2	IMG 1700 H	IMG 2300 H	IMG 2800 H
Attachment operating weight*	4000 lbs	5400 lbs	6600 lbs
Maximum opening	70 in	70 in	80 in
Depth	38 in	42 in	46 in

Loading Jaws	IMG 1700 L	IMG 2300 L	IMG 2800 L
Attachment operating weight*	3950 lbs	5300 lbs	6450 lbs
Load capacity	55000 in ³	82400 in ³	103800 in ³
Maximum opening	100 in	110 in	120 in
Depth	40 in	44 in	48 in


Timber Jaws	IMG 1700 T	IMG 2300 T	IMG 2800 T
Attachment operating weight*	3950 lbs	5300 lbs	6450 lbs
Maximum opening	70 in	70 in	80 in
Depth	38 in	42 in	46 in

N.B. All illustrations and numerical data in this catalog are purely indicative and subject to change at our discretion and without notice. We therefore reserve the right to modify them with a view to improving and continuously developing our product.

compatibility

Suggested uses on machines with an overall weight (in lbs):

■ Best ■ Possible*



*match subject to approval by the Indeco dealer

Accessories

Mounting brackets

Each mounting bracket model can be used with all Indeco products in the same class.



Connecting hoses

We recommend using original Indeco high- and low-pressure hoses to connect various tools to the hydraulic system on the carrier.



Wear blades

Interchangeable and reversible wear blades for greater efficiency and lower maintenance costs; teeth can be mounted.



Quick change teeth - IMG

Teeth with quick-change inserts are available upon request. Easy to replace during maintenance, they are ideal for use in quarries, where the equipment is subject to consistently high levels of wear and tear.





The full range of other Indeco products

Products	Weight	Products	Weight	Products	Weight
IFP 8 X	1650 lbs	IHC 50	450 lbs	ISS*** 20/30	8030 lbs
IFP 13 X	2900 lbs	IHC 70	1000 lbs	ISS*** 25/40	10560 lbs
IFP 19 X	4000 lbs	IHC 75	1100 lbs	ISS*** 30/50	13420 lbs
IFP 28 X	6200 lbs	IHC 150	2150 lbs	ISS*** 35/60	16720 lbs
IFP 35 X	7600 lbs	IHC 250	2850 lbs	ISS*** 45/90	22880 lbs
IFP 45 X	10050 lbs	IHC R 50	950 lbs	IMH 5	1180 lbs
IRP 5 X	1300 lbs	IHC R 70	1400 lbs	IMH 6	1220 lbs
IRP 11 X	2550 lbs	IHC R 75	1500 lbs	IMH 8	1310 lbs
IRP 18 X	3750 lbs	IHC R 150	2650 lbs	IMH 10	1620 lbs
IRP 23 X	5100 lbs	IHC R 250	3350 lbs	IMH 12	2310 lbs
IRP 29 X	6500 lbs	IMG S** 400	850 lbs	IMH 15	3300 lbs
IRP 36 X	7950 lbs	IMG S** 600	1300 lbs	IMH 19	3400 lbs
IRP 45 X	9900 lbs	IMG S** 1200	2550 lbs	IMH 28	4600 lbs
IMP* 15	3300 lbs	IMG S** 1700	3550 lbs	IMH 3.5 SS	2530 lbs
IMP* 20	4600 lbs	IMG S** 2300	4800 lbs	IMH SG16	1850 lbs
IMP* 25	5300 lbs	IMG S** 2800	5850 lbs	IMH SG20	1850 lbs
IMP* 35	7700 lbs	ISS*** 5/7	1250 lbs		
IMP* 45	9900 lbs	ISS*** 10/20	5280 lbs		

*Crusher configuration - **Sorter configuration - ***Third-member configuration

Indeco North America
 135 Research Drive
 Milford CT, 06460
 ph. (203) 713-1030 - fax (203) 713-1040
www.indeco-breakers.com

USA